

F-8196

Identifier: Masao TERAOKA

AMENDMENTS TO THE CLAIMS:

Please replace the claims with the claims provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Cancelled)

2. (Currently Amended) A torque transmission coupling comprising:

input-output rotary members rotatably supported to perform input-output transmission of torque;

5 a frictional engagement section provided between the input-output rotary members to perform torque transmission between the input-output rotary members by enforcing frictional engagement;

10 a compression member set that comprises a pair of members capable of performing relative rotation and that generates thrust through the relative rotation between the members to thereby cause the frictional engagement section to perform the frictional engagement; and

a rotary actuator that causes both of the members of the compression member set to perform engagement-rotational driving whereby to cause the relative rotation;

15 ~~A torque transmission coupling according to claim 1, wherein:~~

the compression member set is a compression gear set that comprises a pair of gears provided as the pair of members, an outer ~~a planetary~~ gear engaged with

F-8196

Identifier: Masao TERAOKA

the gears and an outer gear support ~~a planetary carrier~~ for supporting the outer planetary gear, and that converts an input generated by rotational driving into a compression force in the direction along a rotation axis to thereby cause the frictional engagement section to enforce the frictional engagement, wherein gear ratios or engagement radii between the pair of individual gears and the outer planetary gear are different from each other; any one of the pair of gears, the outer planetary gear, and the outer gear support planetary is non-rotatably supported; any other one thereof is rotationally driven; and the other thereof performs the relative rotation; and

10 the rotary actuator performs the rotational driving; and

the pair of gears comprise a proximal gear and a distal gear;

the distal gear being disposed further from the rotary actuator than the proximal gear; and

the proximal gear having an inner radii that is smaller than the inner radii

15 of the outer gear.

3. (Withdrawn) A torque transmission coupling according to claim 2, wherein:

the rotary actuator performs the rotational driving of the planetary carrier;

the one of the pair of gears is non-rotatably supported;

20 a cam mechanism is interposed between the pair of gears; and

F-8196

Identifier: Masao TERAOKA

the gear ratios between the pair of individual gears and the planetary gear are different from each other.

4. (Currently Amended) A torque transmission coupling according to claim 2, wherein:

5 the rotary actuator performs the rotational driving of the one of the pair of gears;

the outer gear support ~~planetary carrier~~ is non-rotatably supported;

a cam mechanism is interposed between the pair of gears; and

10 the gear ratios or the engagement radii between the pair of individual gears and the outer ~~planetary~~ gear are different from each other.

5. (Withdrawn) A torque transmission coupling according to claim 2, wherein:

15 the rotary actuator performs the rotational driving of the one of the pair of gears;

the other of the pair of gears is non-rotatably supported;

a cam mechanism is interposed between the other of the pair of gears and the planetary carrier; and

20 the engagement radii between the pair of individual gears and the planetary gear are different from each other.

F-8196

Identifier: Masao TERAOKA

6. (Currently Amended) A torque transmission coupling according to claim 2, wherein;

the outer gear support planetary carrier is supported to be capable of performing constant-angle relative rotation;

5 an urging member to be interposed between the outer gear support planetary carrier and a support body side is provided to interfere to rotation with an urging force for the outer gear support planetary carrier that rotates in the same direction at a time of the rotational driving by the rotary actuator;

10 the torque transmission coupling further comprises displacement detection means that detects a displacement amount when the outer gear support planetary carrier performs rotational displacement in resistance with the urging member; and

an engagement force of the frictional engagement section is obtained in accordance with the displacement amount detected

the outer gear support comprises:

15 first and second radially extending plates disposed on axially opposing ends of the outer gear;

a pin connecting the plates and supporting the outer gear;

one of the plates including a cutout, the cutout having a first end disposed between an inner and outer radius of the plate and the cutout
20 extending tangentially from the first end; and

F-8196

Identifier: Masao TERAOKA

the urging member being a biasing member that engages the plate cutout.

7. (Withdrawn) A torque transmission coupling according to claim 3, wherein:

5 the planetary carrier is supported to be capable of performing constant-angle relative rotation;

an urging member to be interposed between the planetary carrier and a support body side is provided to interfere to rotation with an urging force for the planetary carrier that rotates in the same direction at a time of the rotational driving by the rotary actuator;

10

the torque transmission coupling further comprises displacement detection means that detects a displacement amount when the planetary carrier performs rotational displacement in resistance with the urging member; and

an engagement force of the frictional engagement section is obtained in accordance with the displacement amount detected.

15

8. (Currently Amended) A torque transmission coupling according to claim 4, wherein:

the outer gear support planetary carrier is supported to be capable of performing constant-angle relative rotation;

F-8196

Identifier: Masao TERAOKA

an urging member to be interposed between the outer gear support planetary carrier and a support body side is provided to interfere to rotation with an urging force for the outer gear support planetary carrier that rotates in the same direction at a time of the rotational driving by the rotary actuator;

5 the torque transmission coupling further comprises displacement detection means that detects a displacement amount when the outer gear support planetary carrier performs rotational displacement in resistance with the urging member; and an engagement force of the frictional engagement section is obtained in accordance with the displacement amount detected; and

10 the outer gear support comprises:

first and second radially extending plates disposed on axially opposing ends of the outer gear;

a pin connecting the plates and supporting the outer gear;

15 one of the plates including a cutout, the cutout having a first end disposed between an inner and outer radius of the plate and the cutout extending tangentially from the first end; and

the urging member being a biasing member that engages the plate cutout.

20 9. (Withdrawn) A torque transmission coupling according to claim 5, wherein:

F-8196

Identifier: Masao TERAOKA

the planetary carrier is supported to be capable of performing constant-angle relative rotation;

an urging member to be interposed between the planetary carrier and a support body side is provided to interfere to rotation with an urging force for the planetary carrier that rotates in the same direction at a time of the rotational driving by the rotary actuator;

the torque transmission coupling further comprises displacement detection means that detects a displacement amount when the planetary carrier performs rotational displacement in resistance with the urging member; and

an engagement force of the frictional engagement section is obtained in accordance with the displacement amount detected.

10. (Original) A torque transmission coupling according to claim 1, wherein;

the one of the pair of members is supported in the support body side in the direction along the rotation axis; and

the thrust is exerted on the other member as a reaction force with respect to the support body side whereby to cause the frictional engagement to be performed.

F-8196

Identifier: Masao TERAOKA

11. (Currently Amended) A torque transmission coupling according to claim 10, wherein:

the compression member set comprises a pair of gears, ~~an outer planetary gear engaged with the gears and an outer gear support a planetary carrier for supporting the planetary gear~~, converts an input generated by rotational driving into a compression force in the direction along the rotation axis to thereby cause the frictional engagement section to enforce the frictional engagement, wherein any one of the pair of gears, the ~~outer planetary gear~~, and the ~~outer gear support planetary carrier~~ is non-rotatably supported; and any other one thereof is rotationally driven; and the other thereof performs the relative rotation; and gear ratios or engagement radii between the pair of individual gears and the ~~outer planetary gear~~ are different from each other.

12. (Withdrawn) A torque transmission coupling according to claim 11, wherein:

the rotary actuator performs the rotational driving of the planetary carrier; the one of the pair of gears is supported in the support body side to be non-rotatable and in the direction along the rotation axis; a cam mechanism is interposed between the pair of gears; and the gear ratios between the pair of individual gears and the planetary gear are different from each other.

F-8196

Identifier: Masao TERAOKA

13. (Currently Amended) A torque transmission coupling according to claim 11, wherein:

the rotary actuator performs the rotational driving of the one of the pair of gears;

5 the outer gear support planetary carrier is non-rotatably supported in the support body side;

a cam mechanism is interposed between the pair of gears; and

the one of the pair of gears is supported in the support body side in the direction along the rotation axis; and

10 the gear ratios or the engagement radii between the pair of individual gears and the outer planetary gear are different from each other.

14. (Withdrawn) A torque transmission coupling according to claim 11, wherein:

15 the rotary actuator performs the rotational driving of the one of the pair of gears;

the other of the pair of gears is non-rotatably supported in the support body side;

20 a cam mechanism is interposed between the support body side and the planetary carrier ; and

F-8196

Identifier: Masao TERAOKA

the engagement radii between the pair of individual gears and the planetary gear are different from each other.

15. (Original) A torque transmission coupling according to claim 1,
wherein the rotary actuator and the frictional engagement section are disposed with
5 rotation axes thereof being aligned with each other.

16. (Original) A torque transmission coupling according to claim 2,
wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

17. (Withdrawn) A torque transmission coupling according to claim 3,
10 wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

18. (Original) A torque transmission coupling according to claim 4,
wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

F-8196

Identifier: Masao TERAOKA

19. (Withdrawn) A torque transmission coupling according to claim 5,
wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

20. (Original) A torque transmission coupling according to claim 6,
5 wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

21. (Withdrawn) A torque transmission coupling according to claim 7,
wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

10 22. (Original) A torque transmission coupling according to claim 8,
wherein the rotary actuator and the frictional engagement section are disposed with
rotation axes thereof being aligned with each other.

23. (Withdrawn) A torque transmission coupling according to claim 9,
wherein the rotary actuator and the frictional engagement section are disposed with
15 rotation axes thereof being aligned with each other.

F-8196

Identifier: Masao TERAOKA

24. (Original) A torque transmission coupling according to claim 15, wherein a press member is provided between the frictional engagement section and the compression member set, receives the thrust from the compression member set to cause the frictional engagement.

5 25. (Withdrawn) A torque transmission coupling according to claim 1, wherein:
the compression member set is a compression gear set comprising a pair of gears provided as the pair of members;
the rotary actuator comprises a rotational driving shaft tiltedly disposed
10 with respect to the direction along the rotation axis of the compression gear set, and a pair of driving gears fixed to the rotational driving shaft and individually engaged with the pair of gears; and
engagement radii or speed reduction ratios of engagements between the pair of individual gears and the individual driving gears are different from each other.

15 26. (Withdrawn) A torque transmission coupling according to claim 25, wherein the compression gear disposed between the gears set comprises a cam mechanism that causes the thrust to be generated by enforcing the relative rotation.

F-8196

Identifier: Masao TERAOKA

27. (Withdrawn) A torque transmission coupling according to claim 25,
wherein:

one of the gears is supported in a support body side in the direction along
the rotation axis;

5 the other of the gears opposes the side of the friction engagement member;
and

the engagement is performed by moving the other gear toward the friction
engagement member according to the thrust and supporting the one of the pair of
the gears in the support body side.

10 28. (Withdrawn) A torque transmission coupling according to claim 26,
wherein:

one of the gears is supported in a support body side in the direction along
the rotation axis;

15 the other of the gears opposes the side of the friction engagement member;
and

the engagement is performed by moving the other gear toward the friction
engagement member according to the thrust and supporting the one of the pair of
the gears in the support body side.

F-8196

Identifier: Masao TERAOKA

29. (Withdrawn) A torque transmission coupling according to claim 25,
wherein:

at least one of the pair of gears and the pair of driving gears is formed of
face gears; and

5 the engagement radii of the pair of gears and the driving gears are different
from each other.

30. (Withdrawn) A torque transmission coupling according to claim 26,
wherein:

at least one of the pair of gears and the pair of driving gears is formed of
10 face gears; and

the engagement radii of the pair of gears and the driving gears are different
from each other.

31. (Withdrawn) A torque transmission coupling according to claim 27,
wherein:

15 at least one of the pair of gears and the pair of driving gears is formed of
face gears; and

the engagement radii of the pair of gears and the driving gears are different
from each other.

F-8196

Identifier: Masao TERAOKA

32. (Withdrawn) A torque transmission coupling according to claim 25,
wherein:

the pair of gears and the pair of driving gears are formed of crossed gears
or bevel gears; and

5 speed reduction ratios of the pair of gears and the driving gears are
different from each other.

33. (Withdrawn) A torque transmission coupling according to claim 26,
wherein:

the pair of gears and the pair of driving gears are formed of crossed gears
10 or bevel gears; and

speed reduction ratios of the pair of gears and the driving gears are
different from each other.

34. (Withdrawn) A torque transmission coupling according to claim 27,
wherein:

15 the pair of gears and the pair of driving gears are formed of crossed gears
or bevel gears; and

speed reduction ratios of the pair of gears and the driving gears are
different from each other.

F-8196

Identifier: Masao TERAOKA

35. (Withdrawn) A torque transmission coupling according to claim 25,
wherein:

one of the input-output rotary members is a clutch housing, and the other
thereof is a clutch hub disposed on an inner circumference side of the clutch
5 housing;

the friction engagement member is provided between the clutch housing and
the clutch housing;

an compression member opposing the friction engagement member in the
direction along the rotation axis is disposed in an end portion between the clutch
10 housing and the clutch hub; and

the compression member is compressed by the thrust of the compression
gear set.

36. (Withdrawn) A torque transmission coupling according to claim 26,
wherein:

15 one of the input-output rotary members is a clutch housing, and the other
thereof is a clutch hub disposed on an inner circumference side of the clutch
housing;

the friction engagement member is provided between the clutch housing and
the clutch housing;

F-8196

Identifier: Masao TERAOKA

an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch housing and the clutch hub; and

5 the compression member is compressed by the thrust of the compression gear set.

37. (Withdrawn) A torque transmission coupling according to claim 27, wherein:

10 one of the input-output rotary members is a clutch housing, and the other thereof is a clutch hub disposed on an inner circumference side of the clutch housing;

the friction engagement member is provided between the clutch housing and the clutch housing;

15 an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch housing and the clutch hub; and

the compression member is compressed by the thrust of the compression gear set.

38. (Withdrawn) A torque transmission coupling according to claim 29, wherein:

F-8196

Identifier: Masao TERAOKA

one of the input-output rotary members is a clutch housing, and the other thereof is a clutch hub disposed on an inner circumference side of the clutch housing;

the friction engagement member is provided between the clutch housing and
5 the clutch housing;

an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch housing and the clutch hub; and

the compression member is compressed by the thrust of the compression
10 gear set.

39. (Withdrawn) A torque transmission coupling according to claim 32, wherein:

one of the input-output rotary members is a clutch housing, and the other thereof is a clutch hub disposed on an inner circumference side of the clutch
15 housing;

the friction engagement member is provided between the clutch housing and the clutch housing;

an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch
20 housing and the clutch hub; and

F-8196

Identifier: Masao TERAOKA

the compression member is compressed by the thrust of the compression gear set.

40. (Withdrawn) A torque transmission coupling according to claim 33, wherein:

5 one of the input-output rotary members is a clutch housing, and the other thereof is a clutch hub disposed on an inner circumference side of the clutch housing;

 the friction engagement member is provided between the clutch housing and the clutch housing;

10 an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch housing and the clutch hub; and

 the compression member is compressed by the thrust of the compression gear set.

15 41. (Withdrawn) A torque transmission coupling according to claim 34, wherein:

 one of the input-output rotary members is a clutch housing, and the other thereof is a clutch hub disposed on an inner circumference side of the clutch housing;

F-8196

Identifier: Masao TERAOKA

the friction engagement member is provided between the clutch housing and the clutch housing;

an compression member opposing the friction engagement member in the direction along the rotation axis is disposed in an end portion between the clutch housing and the clutch hub; and

the compression member is compressed by the thrust of the compression gear set.

42. (Original) A torque transmission coupling according to claim 1, wherein the torque transmission coupling is disposed to any one of an output side of a transfer device, an input side to a rear differential, a propeller shaft between the transfer device and the rear differential, a front-wheel side acceleration shaft, and rear-wheel side acceleration shaft of a four-wheel drive vehicle.

43. (Original) A torque transmission coupling according to claim 2, wherein the torque transmission coupling is disposed to any one of an output side of a transfer device, an input side to a rear differential, a propeller shaft between the transfer device and the rear differential, a front-wheel side acceleration shaft, and rear-wheel side acceleration shaft of a four-wheel drive vehicle.

44. (New)The coupling of claim 2 further comprising:

F-8196

Identifier: Masao TERAOKA

an exterior housing;

a pinion shaft rotatably connected with the input rotary member;

the pinion shaft being rotatably supported within the housing by a pair of axially spaced bearings; and

5 center axes of each bearing and said pinion shaft being mutually angularly offset.